



LD-80R CABLE
0032-XXXX-00X

0032 - XXXX - XXX

LD-80R UNIVERSAL

FIBER CORE AND TYPE
X=S=STEP INDEX
X=G=GRADED INDEX
X=A=SPECIAL

- 1X 100 MICRONS
- 2X 200 MICRONS
- 4X 400 MICRONS
- 5X 550 MICRONS
- 6X 600 MICRONS
- 8X 800 MICRONS
- 9X 940 MICRONS
- X1 1000 MICRONS
- 12 1250 MICRONS
- 15 1500 MICRONS
- X2 2000 MICRONS

CABLE OVERALL LENGTH

- 02 2 METERS
- 03 3 METERS
- 05 5 METERS
- 10 10 METERS
- 25 25 METERS
- 50 50 METERS

ELECTRICAL VARIATIONS

- 0 NO ELECTRICAL
- 1 THERMAL SENSOR BOTH ENDS
- 2 THERMAL SENSOR/OUTPUT JUMPER
- 3 THERMAL SENSOR & BREAK DETECT

OUTPUT END CONFIG

- 0 STD LD-80R
- 1 LD-80R WITH CONDUCTIVE NUT
- 2 TYPE TH 15mm X 54mm
- 3 TYPE L 10mm NOZZLE
- 4 TYPE D 10mm FLANGED
- 5 TYPE HO 15 X 35mm
- 7 COPPER SMA 905

INPUT END CONFIG

- 0 STD LD-80R
- 1 LD-80R WITH CONDUCTIVE NUT
- 2 TYPE TH 15mm X 54mm
- 3 TYPE L 10mm NOZZLE
- 5 TYPE HO 15 X 35mm
- 6 TYPE L 20mm NOZZLE PLUG/PLAY
- 7 COPPER SMA 905

NEXT ASSEMBLY	DIMENSIONS ARE IN INCHES
	TOLERANCES:
.X ±	ANGLES
.XX ±	.02 ± 1 DEG.
.XXX ±	.005 FINISH
05.19.05	32 ✓
FILE: 32-104	DO NOT SCALE DRAWING

CABLE, LD-80R ROBOTIC UNIVERSAL CONNECTOR	
SCALE: NTS	DRAWN BY: R. LOSCH
MATERIAL: NA	DATE: 10.15.03
FINISH: NA	CHECKED: _____
	APPROVED: _____

RICHARD LOSCH, Inc.	
Bend, Oregon (541) 385-0170	
DWG	REV
A 32-XXXX-XXX	1